

## SB-190 EVERSEAL

**DESCRIPTION:** Versatile, high strength, hard setting, one-part sealant. Superb tensile strength with excellent impact resistance. Water and weather proof.

### USES:

#### Industries

- Automotive
- Construction
- Roofing
- Correctional facilities
- Manufacturing
- Safety surfaces
- Marine

#### Substrates

- Plastic
- Fiberglass
- Metal
- Vinyl
- Glass
- Painted materials
- Cement
- Brick
- Wood

Not recommended for soft expansion joints.

**APPLICATION:** Interface and surfaces must be clean, dry and free of dust, dirt, oil and water proofing and release agents. Cut cartridge nozzle at slant to 1/4" hole and puncture inner seal, apply as desired bead size. Apply uniform bead with steady pressure. Tool immediately after application to ensure full contact with both sides of the joint area. Sealant starts to skin over in 20-25 minutes. Minimum application temperature of 50° F.

### SPECIFICATIONS:

|                   |                  |                         |
|-------------------|------------------|-------------------------|
| Cure Time         | 28 Days          | Using 1/8" Bead         |
| Tack-free Time    | 18-24 Hours      | ASTM-C679 Test Method   |
| Tensile Strength  | 2000 PSI         | ASTM-D412 Test Method   |
| Tear Strength     | Over 300 PLI     | ASTM D-624 Test Method  |
| Elongation        | 500% fully cured | ASTM-D412 Test Method   |
| Staining          | None             | TT-S-00230C Test Method |
| Hardness, Shore A | 70-80            | TT-S-00230C Test Method |
| Viscosity         | Heavy Mastic     |                         |

All values are typical at 75° F, 50% R.H. unless otherwise noted.  
Federal Specifications TT-S-00230C used when applicable.

### FEATURES:

- High strength
- Flexible
- Excellent memory
- Hard setting
- One part
- Weather resistant
- Fast skinning
- Paintable

### BENEFITS:

- Durable bond to material
- Allows for movement of dissimilar materials
- Does not become brittle or crack
- Pick-proof
- Easy application
- Long service life
- Minimizes dirt and dust pickup
- Easy to match substrate

**CLEANING:** While uncured, remove excess material from tools with naphtha or mineral spirits. See cautions on cleaner labels.

**STORAGE:** Unopened containers should be stored in a cool, dry area. Keep above 40° F before use.

**CAUTION:** For industrial use only. Skin and eye irritant. Harmful if swallowed. Avoid contact with or breathing in of vapor and use adequate ventilation. Material on skin should be wiped and washed off with soap and water. For eyes, flush with water and seek medical attention.

SEE MATERIAL SAFETY DATA SHEET.

**PACKAGING:** 10.3 oz. cartridge, 50 gallon drum.

**COLOR:** Clear (Colors on special order).